

309.00 EUR
incl. 19% VAT, plus [shipping](#)



- Slim NUC size Fanless system
- Intel® Bay Trail-M N2930 SoC Processor (1.83GHz, 7.5w)
- 1 * SO-DIMM slot (Max to 8GB)
- 1 * full size Mini PCIe slot for m-SATA Device
- Application: Panel PC, Commerce, Banking, Digital Signage, Gaming, Medical, POS/KIOSK, Industrial Automation, I.O.T, AIO

| | |
|---------------------|---|
| • Dimension (W*D*H) | • 129 * 109 * 34 mm |
| • Construction | • Top cover & I/O plate –aluminum; Base- metal |
| • Colors | • Black / HBJC420U91-2930-B, HBJC420U91W-2930-B |
| • MB model | • JNU91-2930 |
| • CPU | • INTEL® Bay Trail-M N2930 SoC Processor (1.83GHz, 7.5w) |
| • BIOS | • AMI UEFI |
| • Memory | • 1 * SO-DIMM slot (Max to 8GB) |
| • Storage Space | • 1 * full size Mini PCI-E slot for m-SATA Device |
| • Display Interface | • 2 * HDMI |
| • Network | • 1 * RJ45 (Giga LAN) • WiFi (HBJC420U91W-2930-B only) |
| • Audio | • 1 * Line out |
| • Front I/O Port | • 1 * USB 3.0 • 1 * COM |
| • Rear I/O Port | • 2 * USB 2.0, • 2 * HDMI • 1 * GigaLAN, • 1 * Line out • 1 * 12V DC-in |
| • Expansion Slot | • 1 * half size Mini PCI-E slot |
| • Power Source | • DC-12V Jack input • Adapter : AC_90~240V / DC_12V_3A/36W |

| | |
|--------------------|---|
| • Certification | • EMC : CE , FCC • Safety : RoHS , ErP |
| • Environment | • Operating Temperature : -10°C~60°C with air flow (mSATA) • Storage Temperature : -20°C~80°C |
| • Mounting Bracket | • Multiple use bracket (Wall/VESA/DIN Rail) |
| • Packing | • Net Weight■0.9KG • Gross Weight■1.6KG • Color Box Dimension■158(W) x 167(D) x 123.6(H) mm |