

918.00 EUR  
incl. 19% VAT, plus [shipping](#)



- INTEL® BayTrail--M N2930 SOC Chip
- Onboard INTEL® BayTrail-M N2930 1.83GHz Quad Cores CPU
- Onboard SAMSUNG 4G/1333MHz DDR3L Memory
- Support DirectX 11 3D Graphics Acceleration
- Support 1\*Serial ATAII(3Gb/s) Devices
- Support Dual INTEL® Gigabit LAN
- Support CRT Output
- Equipped with 802.11 b/g/n WIFI card & External Antenna
- Support 3\* COM ports■COM2/COM3 Support RS422/485■
- Support 2.5" SATA HDD
- Support 1\*M-SATA Socket
- Support 1\*Mini PCI-E Socket
- Support 3\* USB2.0 Ports
- Support 1\* USB3.0 Port
- Support 3G SIM Card
- Support slick design
- VESA mount(100mm X100mm &75mm x 75mm)

Panel

|                      |                                                         |
|----------------------|---------------------------------------------------------|
| Panel Spec           | AUO G104STN01.0                                         |
| Viewable Size Image  | 10.4 inch With LED Backlight                            |
| Active Area          | 211.2(H) x 158.4(V)                                     |
| Resolution           | 800 x 600 @60Hz                                         |
| Display Color        | 262K                                                    |
| Pixel Pitch          | 0.264 x 0.264 mm                                        |
| Aspect Ratio         | 4:3                                                     |
| Contrast Ratio       | 700:1                                                   |
| Max Brightness       | 400 cd/m <sup>2</sup>                                   |
| Viewing Angle(H/V)   | H160/V130                                               |
| Response Time        | 10ms                                                    |
| Temperature Range    | -30 ~ +80 (Operating)                                   |
| Touch                |                                                         |
| Touch panel style    | 5 wires analog resistive                                |
| Active Range         | 211.58 x 158.75mm ±0.2mm                                |
| Temperature Range    | -10 ~ +60 (Operating)                                   |
| Transparency         | 80 ±3%                                                  |
| Surface Hardness     | 3H (ASTM D3363, pressure 750g/45°)                      |
| Operating Force      | 80g                                                     |
| Knock test           | 10,000,000 times keystrokes                             |
| Case                 |                                                         |
| Panel Material       | Aluminum                                                |
| Case Material        | Iron                                                    |
| Color                | Black                                                   |
| Coating Requirement  | Spray Paint                                             |
| Protection grade IP  | IP65                                                    |
| Speaker              | N/A                                                     |
| Bracket              | 6 (Top:2pcs Side:4pcs, Optional)                        |
| Installation Type    | Open Frame / Wall Hanging (Optional)                    |
| Cooling Mode         | Fan less Fully sealed design                            |
| System Specification |                                                         |
| Form Factor          | 4"                                                      |
| Processor            | INTEL® BayTrail-M N2930 1.83GHz/QC                      |
| System Chipset       | INTEL® BayTrail-M N2930 (SOC)                           |
| System Memory        | 4G/1333MHz DDR3L SAMSUNG DRAM                           |
| BIOS                 | 64MB SPI Flash ROM                                      |
| Ethernet             | 2*INTEL® I211AT Gigabit LAN                             |
| Audio                | Realtek® ALC887 HD Audio                                |
| Storage              | 1* Serial ATA2 3Gb/s connector<br>1* M-SATA connector   |
| WIFI Module          | N/A(Optional)                                           |
| Optical Device       | N/A                                                     |
| Expansion            | PCI-E mini card for WLAN                                |
| Display Output       | CRT                                                     |
| I.O Port             | 1*USB3.0 3*USB2.0 1*RS232<br>2*RS232/422/485 1*Line-out |
| Power Adapter        | DC-IN (9~24V, Euro terminal block)                      |
| OS Support           | Windows 7/8/8.1                                         |
| Temperature          | Operating -10 ~ +60                                     |
| Humidity             | 20%~90% (non condensing)                                |
| Shock                | Operating 15G 11ms duration                             |
| Vibration            | Operating 5~500Hz/1 Grms                                |
| Net Weight (kg)      |                                                         |
| Dimension            | 284.0mm*230.0mm*37.0mm                                  |
| Certification        | FCC CE IP65                                             |

|                   |                                                                                           |
|-------------------|-------------------------------------------------------------------------------------------|
| Other             | Support Non wire I.O interface output                                                     |
| Other Information |                                                                                           |
| Application       | Commercial ■ Banking ■ Digital Signage                                                    |
|                   | POS/KIOSK ■ Industrial Automation                                                         |
| Special Features  | Metal design, compact ■ slick                                                             |
| Other             | Optional wall hanging telescopic bracket, etc., can also be used as the embedded security |
| Accessory         |                                                                                           |
| Adapter           | 1* 60W AC-DC Adapter                                                                      |
| Power cord        | 1*Power cord                                                                              |
| Manual            | 2*Manual                                                                                  |
| CD                | 1*CD                                                                                      |
| Other             | 2* WI-FI antenna                                                                          |