

DSS-1200

Digital Signage Player base on Intel Core i3 / i5 / i7 Calpella Platform



System

CPU	Proprietary motherboard, Intel® Calpella platform Support Arrandele rPGA socket type processor
Memory	2 x SO-DIMM DDR3 800/1066/1333 up to 8GB
Chipset	Intel HM55 chipset
Expansion Slot	2 x half size mini PCIe slot (Optional for 3G/WiFi module) 1 x SIM card slot (for 3G appliance) support user accessible
Cooling	System Fan with smart FAN function

I/O panel

Front I/O	3 x 3.5mm Phone Jack, support 5.1 channel audio output 1 x eSATA and USB 2.0 combo connector 3 x USB 2.0 1 x Power LED 1 x Storage status LED (HDD/Card Reader) 1 x WiFi status LED 1 x Reset Button 1 x Power Button 1 x 3 in 1 Card Reader (SD / MMC / MS)
Rear I/O	1 x DC JACK for DC12V single power input 1 x DVI-I for DVI-D or VGA output 1 x HDMI (V1.3 compatible) 1 x RJ-45 GbE port 2 x USB 2.0 1 x COM Port support RS-232/422/485 (offer +5V/+12V output selection) 2 x WiFi external antenna (optional) 1 x 3G external antenna (optional) 1 x S/PDIF Output

Features

- Compact Size with Intel® Calpella Platform
- Support Intel Core i3 / i5 / i7
- 2 x SO-DIMM DDR3 800/1066/1333 up to 8GB
- 1 x DVI-I, 1 x HDMI, 1 x GbE & 5.1 channel audio
- 1 x eSATA & USB Combo Connector
- 3-in-1 Card Reader and 5 x USB
- Optional WiFi or 3G Module

Storage

Type	1 x 2.5" Hard Drive Bay (SATA)
-------------	--------------------------------

Qualification

Certification	CE/FCC, Class A
----------------------	-----------------

Environmental

Operating Temp.	0 ~ 40°C, 0 - 90%, non-condensing
Storage Temp.	-20°C to 80°C, 0 - 90%, non-condensing
Power Adapter	Input : 100-240 VAC, 50-60 Hz Output : 65W +12VDC/5.4A output

Mechanical

Construction	Metal Housing
Mounting	Wall-Mount, VESA Mount
Weight	1.0 kg
Dimension	200 x 153.3 x 35 mm (WxDxH)

Ordering Information

Part Number	DSS-1200
Description	Digital Signage Player base on Intel Core i3 / i5 / i7 Calpella Platform